



Bitumen

60/70

Bitumen Types and Their Uses:

- *Paving Grades* - road surfacing, and some industrial applications
- *Hard Grades* - paints and enamels etc
- *Oxidized/Blown Grades* - roofing, waterproofing, electrical products, and many others
- *Cutback Bitumen* - spraying and some mixing applications
- *Bitumen Emulsions* - used largely in road surfacing applications
- *Polymer Modified Binders (PMBs)* - there are different types and they can be used for many of the applications mentioned above

Index:

Penetration Bitumen 60/70	Specification	Test Method
<i>Specific Gravity @ 25/25 C</i>	<i>1.01-1.06</i>	<i>D-70</i>
<i>Penetration @ 25 C</i>	<i>60/70</i>	<i>D-5</i>
<i>Softening Point C</i>	<i>49/56</i>	<i>D-36</i>
<i>Ductility @ 25 C</i>	<i>100 Min</i>	<i>D-113</i>
<i>Loss On Heating (wt)%</i>	<i>0.2 Max</i>	<i>D-6</i>
<i>Drop In Penetration After Heating %</i>	<i>20 Max</i>	<i>D-6 & D-5</i>
<i>Flash Point C</i>	<i>250 Min</i>	<i>D-92</i>
<i>Solubility In CS (wt)%</i>	<i>99.5 Min</i>	<i>D-4</i>
<i>Spot Test</i>	<i>Negative</i>	<i>*A·A·S·H·O·T·102</i>

Description:

Bitumen suitable for road construction and for the production of asphalt pavements with superior properties. Penetration Grade bitumen's are specified by the penetration and softening point test. Designation is by penetration range only. The penetration grade bitumen's have a thermoplastic property which causes the material to soften at high temperatures and to harden at lower temperatures.

AZURE VISION Sdn Bhd

A4-2-7 Solaris Dutamas, No.1, Jalan Dutamas 1, 50480, Kuala Lumpur

Tel : +603 62 112 110

Fax : +603 62 0789 77

Website : www.azurevision.com.my

Email : info@azurevision.com.my