

GROUP	PRODUCT	Appearance	Color ASTM D-1500	Density at 15°C ASTM D-1298	Kinematic Viscosity ASTM D-445		Viscosity Index ASTM D-2270	Flash Point (°C) ASTM D-92	Pour Point (°C) ASTM D-97
					at 40°C (Cst)	at 100°C (Cst)			
GROUP - I	SN-65	Clear & Bright	L 1.0	Report	Min 7.50	Min 2.28	Min 90	Min 160	Max -3
	SN-100	Clear & Bright	L 1.5	Report	Min 23.0	Min 4.00	Min 90	Min 170	Max -3
	SN 150	Clear & Bright	L 2.0	Report	Min 28.0	Min 5.00	Min 90	Min 200	Max -3
	SN 500	Clear & Bright	L 2.5	Report	Min 103	Min 11.0	Min 90	Min 240	Max -3
	Bright Stock 150	Clear & Bright	L 3.5	Report	Min 450	Min 30.0	Min 90	Min 270	Max -3
GROUP - II	N-150	Clear & Bright	L 0.5	Report	Min 28.0	Min 4.70	Min 95	Min 206	Max -12
	N-500	Clear & Bright	L 0.5	Report	Min 90.0	Min 11.0	Min 95	Min 240	Max -12
GROUP - III	4-Cst	Clear & Bright	L 0.5	Report	Min 18.0	Min 4.00	Min 120	Min 200	Max -12
	6-Cst	Clear & Bright	L 0.5	Report	Min 31.5	Min 5.80	Min 125	Min 218	Max -12
	8-Cst	Clear & Bright	L 0.5	Report	Min 42.0	Min 7.50	Min 128	Min 240	Max -12